



TECHNICAL INFORMATION

Excellence in Electronics

TRIODE

TYPE

CK5842

The CK5842 (417A) is a heater-cathode type, high transconductance triode of miniature construction. The design features of low noise, low interelectrode capacitances, and very high transconductance make this type suitable for service in wide band amplifier stages, and especially grounded-grid operation. The useful frequency range extends from low to very high frequencies. The heater-cathode construction is designed to withstand many thousands of cycles of intermittent operation.

MECHANICAL DATA

ENVELOPE: T-6½ Glass

BASE: Miniature Button 9-Pin.

TERMINAL CONNECTIONS:

Pin 1 Plate	Pin 6 Cathode
Pin 2 No Connection	Pin 7 Grid
Pin 3 Heater	Pin 8 Grid
Pin 4 Grid	Pin 9 Heater
Pin 5 Grid	

MOUNTING POSITION: Any

ELECTRICAL DATA

DIRECT INTERELECTRODE CAPACITANCES: (μfds)

Plate to Cathode and Heater
Input (k to g + h)
Output (p to g + h)

Without Shield

0.55 max.
9.0
1.8

RATINGS—ABSOLUTE MAXIMUM VALUES:

Heater Voltage (ac or dc)
Plate Voltage
Plate Dissipation
Cathode Current
Heater-Cathode Voltage
Bulb Temperature

6.3±10% volts
200 volts
4.5 watts
38 ma
55 volts
160 °C



CHARACTERISTICS AND TYPICAL OPERATION:

Heater Voltage
Heater Current
Plate Voltage
Cathode Bias Resistance
Grid Voltage
Plate Current
Plate Resistance
Transconductance
Amplification Factor

6.3
0.3
150
60
0
25
1700
25,000
43

6.3 volts
0.3 ma
130 volts
360 ohms
+9 volts
27 ma
1600 ohms
27000 umhos
43

300 M2



BOTTOM VIEW

9V

Printed in
U.S.A.

Tentative Data


RAYTHEON MANUFACTURING COMPANY

RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS

NEWTON 58, MASS.



TRIODE




RAYTHEON MANUFACTURING COMPANY
RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS



TYPE CK5842

TRIODE



Made in
U.S.A.


RAYTHEON MANUFACTURING COMPANY
RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS

NEWTON 58, MASS.



TRIODE

AVERAGE CHARACTERISTICS




RAYTHEON MANUFACTURING COMPANY
RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS



TYPE CK5842

TRIODE

AVERAGE CHARACTERISTICS




Printed in
U.S.A.

RAYTHEON MANUFACTURING COMPANY
RECEIVING TUBE AND SEMICONDUCTOR OPERATIONS

NEWTON 58 MASS



TRIODE



RAYTHEON MANUFACTURING COMPANY
VACUUM TUBE AND SEMICONDUCTOR OPERATIONS

RAYTHEON

TECHNICAL
INFORMATION
SERVICE

Technical Information

RELIABILITY CONTROL SUPPLEMENT

5842

RELIABILITY
CONTROLLED
10,000 HOUR LIFE
TRIODE

RELIABILITY CONTROLLED 10,000 HOUR LIFE

Type 5842 is one of Raytheon's Reliability Controlled tubes and is warranted* for 10,000 hours of useful life when operated under the following approved conditions:

$E_f = 6.3V \pm 5\%$; $E_b = 150 Vdc$; $E_c = 0$; $R_k = 60 \text{ ohms}$.

To control reliability a randomly selected statistical sample is operated under above conditions plus an E_{hk} of 100 Vdc and an R_g of 0.47 meg. for 10,000 hours. The Reliability Controlled 10,000 Hour Life Test end points are:

Transconductance	17,500 umhos, min.
Heater-cathode leakage	10 uAdc, max.
Grid current	-1.0 uAdc, max.

*Long Life Warranty is applied to lots of 100 tubes minimum. Raytheon warrants these tubes to have an average useful life of over 10,000 hours. The end of useful life may be considered to have been reached when transconductance under normal test conditions falls below 17,500 umhos. See "10,000 Hour Reliable Life Certificate for Reliability Controlled Tubes" for warranty details.

Printed in
U.S.A.